



MODEL
C300V

KEL-BERG 3-AXLE CONTAINER
CHASSIS

TRAILER SPECIFICATION

KEL-BERG 3-AXLE CONTAINER CHASSIS

DIMENSIONS & WEIGHTS:

Wheelbase	8,130 mm
Bogie	2 x 1,310 mm
Coupling height	1,150 mm
Front overhang	825 / 1,125 mm
Rear overhang	1,620 mm
Bottom height in the rear	1,342 mm
Neck length	3,720 mm

Permissible total weight	42,000 kg
Permissible king pin weight	18,000 kg
Permissible towbar weight	24,000 kg

CHASSIS:

Chassis centre beam is welded high-strength steel with sections that slide into each other. This chassis is suitable for heavy-duty applications. The U-rail on the neck bend is suitable for installation of aluminium ramps.

AXLES:

Fitted with 3 x 9 ton SAF axles with disc brakes, raise / lower valve and liftable 1st axle.

TYRES & WHEELS:

Fitted with 6 M&S tyres 385/65R22.5 mounted on steel rims.

BRAKES:

Fitted with Knorr / WABCO EBS braking system.



TRAILER SPECIFICATION

KEL-BERG 3-AXLE CONTAINER CHASSIS

MUDGUARDS:

Fitted with 180 degree mudguards on all axles. Anti-spray mud flaps on 3rd axle.

LANDING LEGS:

Fitted with 2 landing legs of recognised brand with 2 speed raise and lower with S-foot.

PAINTING:

KTL painted in RAL 3020 colour.

ELECTRICAL SYSTEM:

The electrical system is manufactured according to ISO 3731. It features:

- 2 pcs 5-chamber rear lights
- 2 number plate lights
- 2 x swivelling lights
- 5 side marker lights with reflectors per side
- Statutory marker lights and statutory reflectors
- 2 x 7-pin light sockets
- VBG light sockets
- VBG duo-matic air plug

CONTAINER LOCKS:

For 1 x 40 ft container.

For 2 x 20 ft containers.

KINGPIN:

Fitted with 2" kingpin.

