

KEL-BERG
NORGE

WEB: www.kelberg.no



MODEL
D18

KEL-BERG 3-AXLE DOLLY

TRAILER SPECIFICATION

KEL-BERG 3-AXLE DOLLY

DIMENSIONS & WEIGHTS:

Coupling height	1,200 mm
Coupling length	3,700 mm
Wheelbase	1,310 mm

Permissible total weight	18,000 kg
Permissible total axle load	18,000 kg
Unladen weight	2,880 kg

CHASSIS:

Longitudinal members welded to I-profile in high strength steel. Features heavy duty cross members and reinforcements. EU approved underrun bumper.

AXLES:

Fitted with 2 x 9 ton BPW or SAF axles with drum brakes.

TYRES & WHEELS:

4 pcs tyres 385/65R22.5 of recognised brand mounted on silver steel rims.

BRAKES:

Fitted with 2 line compressed air system, parking brakes and shunting valve. EBS system includes axle sensors. WABCO / Knorr components used.

MUDGUARDS:

4 pcs 180 degrees plastic mudguards with 2 pcs mud flaps.



LANDING LEGS:

1 landing leg with wheels. Mechanically operated and mounted to chassis front.

PAINTING:

All components are steel blasted and primed with anti-corrosion primer. Painted in approved ICI / PPG 2-component products. Aluminium components are anodised.

COUPLING:

Fitted with 57.5 mm VBG coupling. Length from drawbar eye to coupling centre – 3,700 mm. Features:

- 2 pcs air hoses with duomatic
- 2 pcs 7-pole light sockets
- 1 EBS cable routed to the drawbar eye in a protective pull tube.

COUPLING & SWIVEL RING:

Double ball swivelling ring with lock mounted with swivelling coupling.

ELECTRICAL SYSTEM:

- 24-volt system ISO st VZO. standard
- 4 pcs. 3-chamber lights
- 2 pcs. reversing lights, cornering lights, side marker lights and licence plate lights from HELLA/Aspöck
- Fully fitted with reflectors
- 2 x 7-pole light sockets fitted according to ISO 3731

EXTRAS:

- Raise / lower valve
- EBS cable
- 2 pcs spiral air hoses
- 2 pcs 7-pin spiral cable mounted in front of the swivelling coupling for use with the trailer.

